



DECLARATION OF PERFORMANCE

Nº: 2013/F/80/A

Ed: 4

1. Product type and identification

G80, EPDM waterproofing membrane (0.80 mm thick)

2. Name and contact address of the manufacturer

FIRESTONE BUILDING PRODUCTS SPAIN
Av Diagonal 672 bajos
E-08034 Barcelona

3. Intended use

EN 13984 Vapour control layer (Type A)

4. System of assessment and verification of constancy of performance (AVCP)

3

5. Notified body

Tests carried out at 0370

6. Declared performance

Essential characteristics	Performance	Test standard	Harmonised technical specification
Reaction to fire	E	EN 13501-1	EN 13984:2013
Watertightness (2 kPa)	Pass	EN 1928	
Water vapour permeability	50.000	EN 1931	
Impact resistance	NPD	EN 12691	
Joint shear resistance	NPD	EN 12316-2	
Tensile strength	≥ 7 MPa	EN 12311-2	
Elongation	≥ 300%	EN 12311-2	
Tear resistance	≥ 10 N	EN 12310-2	
Durability against ageing	Pass	EN 1296/EN 1931	

The performance of the product identified in point 1 is in conformity with the declared performance in point 9.

This declaration of performance (DoP) is issued under the sole responsibility of the manufacturer identified in point 6.

Signed for and on behalf of the manufacturer by:

David Pelejero
Quality Manager

Terrassa, February 2015